Product data sheet Characteristics

TSXRKY8EX

extendable rack - for multi-racks configuration - 8 slots - IP20



Commercial status

Discontinued: 31 December 2018

(!) Restricted Sales for Services

Main

Range of product

Product or component type	Extendable rack	
Product specific application	For multi-racks configuration	
Complementary		
Number of slots	8	
Product compatibility	I/O module	
	Specific application module	
	TSXP57 processor	
	TSXPSY power supply	
Electrical connection	2 connectors female SUB-D 9 (remote connection of bus X)	

Modicon Premium Automation platform

By 4 M6 screws (panel)

	By clips (35 mm symmetrical DIN rail)
Marking	CE
Net weight	1.78 kg

Environment

Fixing mode

		0
Standards	89/336/EEC	
	93/68/EEC	2
	73/23/EEC	-
	CSA C22.2 No 142	۷.
	CSA C22.2 No 213 Class I Division 2 Group C	2
	UL 508	, ,
	92/31/EEC	4
	CSA C22.2 No 213 Class I Division 2 Group A	hstitute e
	CSA C22.2 No 213 Class I Division 2 Group B	Ģ.
	·	n n
	IEC 61131-2	S.
	CSA C22.2 No 213 Class I Division 2 Group D	ded
Product certifications	RMRS	
	ABS	. <u>.</u>
	RINA	. <u>v</u>
	DNV	
	GL	ţ <u>t</u>
	BV	Ā
	LR	noch
Ambient air temperature for operation	060 °C	—— <u>sid</u>
Ambient air temperature for storage	-2570 °C	
Relative humidity 1095 % without condensation for operation		

5...95 % without condensation for storage

Operating altitude	02000 m
Protective treatment	TC
IP degree of protection	IP20
Pollution degree	2

Contractual warranty

Warranty	18 months	

TSXRKY8EX is replaced by:

Standard environment BMEXBP0800

rack X80 - 8 slots - Ethernet backplane

Qty 1

Reason for Substitution: End of life | Substitution date: 31 December 2018

