
Product data sheet Characteristics

TSXRKY12EXC

extendable rack - for multi-racks configuration - 12 slots - IP20



(!) Restricted Sales for Services

Main

Range of product

Product or component type

Product specific application	For multi-racks configuration	
Complementary		i caco
Number of slots	12	- v
Product compatibility	Specific application module I/O module TSXPSY power supply TSXP57 processor	iliv of these or
Electrical connection	2 connectors female SUB-D 9 (remote connection of bus X)	<u></u>
Fixing mode	By 4 M6 screws (panel) By clips (35 mm symmetrical DIN rail)	hility or r
Marking	CE	
Net weight	2.34 kg	

Modicon Premium Automation platform

Extendable rack

Environment

Standards	CSA C22.2 No 213 Class I Division 2 Group A	<u>v</u>
	CSA C22.2 No 213 Class I Division 2 Group C	ق ر
	73/23/EEC	not to be
	93/68/EEC	<u>.v.</u>
	CSA C22.2 No 142	and Dur
	UL 508	Ę.
	92/31/EEC	= e
	IEC 61131-2	substitute for and
	CSA C22.2 No 213 Class I Division 2 Group B	
	CSA C22.2 No 213 Class I Division 2 Group D	S
	89/336/EEC	documentation is not intended as
Product certifications	DNV	ten
	GL	.= 5
	RMRS	. <u>v</u> .
	RINA	i.
	BV	ntai
	ABS	ine ine
	LR	doci
Ambient air temperature for operation	060 °C	This
Ambient air temperature for storage	-2570 °C	ii.
Relative humidity	1095 % without condensation for operation	Disclaimer

5...95 % without condensation for storage

Operating altitude	02000 m
Protective treatment	TC Conformal coating Humiseal 1A33
IP degree of protection	IP20
Pollution degree	2

Contractual warranty

Warranty	18 months

TSXRKY12EXC is replaced by:

Harsh environment BMXXBP1200H

ruggedized rack M340 -12 slots - panel or plate mounting

Qty 1

Reason for Substitution: End of life | Substitution date: 31 December 2017

